



RG -59 COAXIAL WITH 0.5MM POWER CABLE

<u>SPECIFICATION</u>	
Centre Conductor	0.81 MM 21% CONDUCTIVITY
Dielectric Core	3.75 MM Foam
Foil	Copper Colour ALU/Pet Foil
Braid	112/0.12 MM Copper Plated ALU Wire
Jacket	Black PVC
Size	300 / 100 Yards
Colour	Black PVC
<u>Frequency (MHz)</u>	<u>ATTENUATION</u> Max value (dB / 100 M)
5 MHz	3.05 dB / 100 M
55 MHz	6.85 dB / 100 M
211 MHz	12.55 dB / 100 M
270 MHz	13.95 dB / 100 M
300 MHz	14.6 dB / 100 M
330 MHz	15.29 dB / 100 M
350 MHz	15.75 dB / 100 M
400 MHz	16.73 dB / 100 M
450 MHz	17.72 dB / 100 M
500 MHz	18.7 dB / 100 M
550 MHz	19.52 dB / 100 M
600 MHz	20.34 dB / 100 M
750 MHz	22.87 dB / 100 M
870 MHz	24.85 dB / 100 M
1000 MHz	26.64 dB / 100 M
1300 MHz	30.6 dB / 100 M
1450 MHz	32.8 dB / 100 M
1750 MHz	35.8 dB / 100 M
2150 MHz	39.7 dB / 100 M
2600 MHz	42.81 dB / 100 M
2832 MHz	44.48 dB / 100 M
3000 MHz	46.9 dB / 100 M